



PRODUCT SPECIFICATION

Product Name: lithium manganese dioxide battery

Type: CR2032HT

VERSION: 2018

Author :	Date :
Auditor :	Totalpages: 4

Customer Name:

1. Scope

This specification governs the performance of the following
Akyga Battery model: CR2032HT.

Lithium Button Cell

Designations:

Akyga Battery CR2032HT

Nominal Voltage: 3V

Typical Weight: 3 g

2. Technique parameter

Item		Unit	Standard
Dimensions	Diameter	mm	20 (-0.2)
	Height		3.2(-0.2)
Open voltage		V	3.1-3.45
Instant short-circuit current		mA	≥300
Nominal capacity (Load 15KΩ)		mAh	240
Appearance	The outward appearance is smooth, bright and clean, no rusty stain		
Min time of discharge	Initial stage (New battery)	h	1200
	Delayed for 12 months		1140
Over-discharge Characteristics		No leakage	
Operating Temperature Range		-40°C ~85°C	

3、 Test method

No.	Item	Condition
1	Dimensions	When measure with vernier calipers whose precision is up 0.02mm. to avoid short circuit,should paste on one insulation material on one end of the vernier calipers
2	Open voltage	the precision of multimeters is not lower than 0.25%,intel resistance is bigger than 1MΩ
3	Instant short-circuit current	When test with multimeters, not surpass 0.5 second each time, avoid duplicating tests, if need once more, the time-gap should above half hour
4	Appearance	visual
5	Min time of discharge	Takes 9 batteries stochastically, Lay aside above 8 hours in the temperature of $20 \pm 2 \text{ }^\circ\text{C}$ and under the humidity of $60 \pm 15\%$ conditions, with the condition that Resistance is 15 kΩ ,end-point voltage is 2.0V. The new battery (Initial stage)should be tested in 60 days after produce. The old battery (Delayed for 12 months) should be tested in 14 days after the storage period.
6	Over-discharge Characteristics	Take nine battery in the temperature of $20 \pm 2 \text{ }^\circ\text{C}$ and under the humidity of $60 \pm 15\%$ conditions, with the condition that Resistance is 15 kΩ ,end-point voltage is 1.2V. visual test.

4、 Acceptance rule

Check Criterion: ISO2859-1:1999(GB/T2828.1-2003),

The concrete item see the sheet of the following :

NO.	Check item	IL	AQL
1	Dimensions	I	Sampling 20
2	Open voltage		0.25
3	Appearance	II	Cr
			Maj
			Min

5、Cautions for Use

- 5.1 The battery shall be installed with its “+” and “-“ polarity in a correct position, otherwise may cause short-circuit.
- 5.2 Short-circuiting, heating, disposing of into fire or disassembling of battery is prohibited.
- 5.3 Battery can not be forced discharged, which leads to excess gassing and may result in bulging, leakage or explosion.
- 5.4 New batteries and used ones can not be used at the same time. It is recommended to use the same brand when replacing batteries.
- 5.5 Direct soldering is not allowed, or else it will damage the battery.
- 5.6 Battery are to be kept away from children. If swallowed, contact a physician at once.

6、Storage Environment

The environment temperature at 0 to 30 °C , RH not more than 75% is proper.Keep the environment sweep、cool、dry、 well ventilated and should not close to heat high and wet place.

7、Marking and package

Basis customer request

8、Discharge Characteristics (Initial stage, Load 15KΩ,24h /d, EPV 2.0 V)

