

	₽	
יופרים שמורגיל ו בשבי לבתי אבלו מתכרנוטו כו וששתב כם מווים לחתי	rm whatever is not permitted without written authority from th	
3	÷	
3	£	
3	ě	
3	ŧ	
0	6	
5	ž	
5	Ŧ	
3	4	
3	Š	
5	ŧ	operty of FCI. Copyright FCI.
Ž	ō	
	ţ	ž
è	Ē	Ĭ
ū	ă	é
0	ţ	ŏ
-	č	ت
7	<u>v</u>	Ë
=	ě	4
n	ě	0
3	ĕ	÷
Ď	*	ĕ
-	٤	ö

В

PRODUCT NUMBER	POS	DIM "A"	DIM "C"	DIM "D"	DIM "E"
919TC-WXY09	9	.366 [9.30]	.157 [4.00]	.118 [3.00]	.1990 [5.055]
↑ -WXY09LF		.500 [5.50]	.137 [4.00]	.110 [3.00]	.1990 [5.055]
-WXY11	11	406 [10 70]	107 [5 00]	157 [4 00]	2790 [6 045]
-WXY11LF	11	.406 [10.30]	.197 [5.00]	.157 [4.00]	.2380 [6.045]
-WXY15	15	.484 [12.30]	.276 [7.00]	.236 [6.00]	.3170 [8.052]
-WXY15LF	2	.404 [12.50]	.270 [7.00]	.230 [0.00]	.5170 [8.052]
-WXY21	21	.602 [15.30]	.394 [10.00]	.354 [9.00]	.4350 [11.049]
-WXY21LF		.002 [10.00]	.001 [10.00]	.554 [5.55]	.1000 [11.010]
-WXY25	25	691 [17 70]	472 [12.00]	477 [11 00]	5140 [13.056]
-WXY25LF	25	.681 [17.30]	.472 [12.00]	.433 [11.00]	.5140 [13.056]
-WXY31	31	.800 [20.30]	.591 [15.00]	.551 [14.00]	.6320 [16.053]
-WXY31LF		.000 [20.00]	.001 [10.00]	.001 [11.00]	.0020 [10.000]
-WXY41	41	.996 [25.30]	.787 [20.00]	.748 [19.00]	.8290 [21.057]
-WXY41LF		.550 [25.50]	.707 [20.00]	., 10 [10.00]	.0200 [21.007]
-WXY51	51	1.193 [30.30]	.984 [25.00]	.945 [24.00]	1.0260 [26.060]
-WXY51LF		1.195 [50.50]	.904 [23.00]	.943 [24.00]	[1.0200 [20.000]
-WXY69	69	1.547 [39.30]	1.339 [34.00]	   1.299	1.3800 [35.052]
V −WXY69LF		[00.00]			[00.002]

STATEMENT: "THIS PRODUCT MEETS THE REQUIREMENTS OF THE EUROPE UNION DIRECTIVE OF RESTRICTIONS FOR HAZARDOUS SUBSTANCES (DIRECTIVE 2002/95/EC) AND CAN BE PROCESSED IN THE PROCESS CONDITIONS FOR WHICH THE PRODUCT IS DEVELOPED. FCI, ITS SUBSIDIARIES AND AFFILIATES ("FCI") PROVIDES THE ABOVE DATA AND INFORMATION IN GOOD FAITH BASED UPON CURRENT KNOWLEDGE AND EXPERIENCE, BUT MAKE NO WARRANTY THAT SUCH DATA OR INFORMATION IS FREE FROM ERROR, IS COMPLETE OR IS SUFFICIENT FOR USER'S INTENDED PURPOSE EVEN IF MADE KNOWN TO FCI. FCI SPECIFICALLY DISCLAIMS ANY WARRANTY, EXPRESS OR IMPLIED, AND ASSUMES NO LIABILITY WITH RESPECT TO THE EFFECTIVENESS OR SAFETY OF THE PRODUCTS LISTED ABOVE. EACH USER MUST MAKE ITS OWN DETERMINATION AS TO THE SUITABILITY OF FCI'S PRODUCTS AND MATERIALS FOR ITS OWN PARTICULAR PURPOSE, AND MUST ASSURE THAT ITS PRODUCTS FABRICATE FROM FCI'S PRODUCTS AND MATERIALS ARE SAFE AND LAWFUL. IT IS THE USER'S RESPONSIBILITY TO ASSURE PROPER USE ABS DISPOSAL OF FCI'S PRODUCTS AND MATERIALS, THE SAFETY AND HEALTH OF USER'S EMPLOYEES AND CUSTOMER, AND USER'S COMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS...

## NOTES:

## 1. MATERIALS:

RECEPTACLE HOUSING - LCP. COLOR: NATURAL. RECEPTACLE TERMINALS - COPPER ALLOY.

TIN LEAD PLATING: PLATED WITH 15u"/.38u GXT IN CONTACT AREA AND 100u"/2.54u SnPb ON SOLDER LEGS WITH AN OVERALL 50u"/1.27u Ni UNDERPLATE.

LEAD FREE PLATING: 100u"/2.54u PURE TIN PLATING ON SOLDER LEGS AN OVERALL 50u"/1.27u Ni UNDERPLATE.

HEADER HOUSING - LCP. COLOR: NATURAL HEADER TERMINALS - COPPER ALLOY.

TIN LEAD PLATING: PLATED WITH 15u"/.38u GXT IN CONTACT AREA AND 100u"/2.54u SnPb ON SOLDER LEGS WITH AN OVERALL 50u"/1.27u Ni UNDERPLATE.

LEAD FREE PLATING: 100u"/2.54u PURE TIN PLATING ON SOLDER LEGS AN OVERALL 50u"/1.27u Ni UNDERPLATE.

RETENTION DEVICE - BRASS,


TIN LEAD PLATING: PLATED WITH 100u"/2.54u SnPb OVER NICKEL. LEAD FREE PLATING: PLATED WITH 100u"/2.54u Sn OVER NICKEL.

- 2. REFERENCE GS-12-006 FOR PRODUCT PERFORMANCE DATA.
- (3) SEE TA-774 FOR FURTHER DESCRIPTION OF HOW THIS DIMENSION IS APPLIED.
- (4) PICK AND PLACE CAP OR TAPE IS ONLY AVAILABLE WITH OPTION 3 PACKAGING. (PSA ADHESIVE SEALED).
  ALSO, PSA PACKAGING REQUIRES A PICK AND PLACÉ CAP.
- 5. RECOMMENDED SOLDER PASTE THICKNESS IS .006 TO .008 INCHES THICK.
- (6.) THE TOE HEIGHT OF THE SOLDER TAIL SHALL BE MEASURED FROM THE LOWEST POINT OF THE .004
  CO-PLANARITY GRAVITY PLANE. THIS MEASUREMENT
  IS NOT TO EXCEED A WINDOW OF .000 TO .007 INCHES.
- (7) THREE SLOTS MAY BE LOCATED AT EITHER END OF HOUSING.
- (8) 5.50mm MATED HEIGHT IS ONLY AVAILABLE IN 9, 15 AND 31 POS.
- (9), 7.50mm MATED HEIGHT IS ONLY AVAILABLE IN 9 POS.
- (1) APPLIES TO 91921-3XYZZ AND 91931- 3XYZZ OPTIONS ONLY.
- 1 PART NUMBER WITH LEAD FREE IN TIN LEAD END ARE LEAD FREE OPTION. SEE CONAN ASSY P/N NUMBERS
- 12. THE HOUSING WILL WITHSTAND EXPOSURE TO 260° PEAK TEMPERATURE FOR 30 SECONDS IN A CONVENTION INFRA RED OR VAPOR PHASE REFLOW OVEN.

mat'l. code —					tolerances unless otherwise specified						CUSTOMER				4							1	
ltr	ecn	no	dr	date			.xx	±.01	±.01/.X±.3		COPY		FCI				www.fciconnect.com						
AA					linear	· $\square$	.XXX ±.005/			XX ±.005/.XX±.13		ection	1	title CONAN <sup>TM</sup> CONNE			-OTOD						
						.xxxx ±.0020/.xxx±.051																	
					angle	s	0° ±2				7	グユ	7				<u> 4SS</u>	<u> SEM</u>	BL'	<u>Y</u>			
					dr	dr R.SEIPLE 0		01/1	13/91						CONAN			cod	code				
					engr	engr D.HORCHLER D			þ1/1			0/92	size dwg no					213					
					chr	D.HORCHLER 01/10/92 D.HORCHLER 01/10/92		4		,	0		10	1900			sheet 6 of 7		1				
					appd					Α		J	٦	300									
she	et	revis	ion																				]
inde	x	shee	t																				
		A C A	Т.								3						code 22	526	 3			4	_

1 | 2

ACAD PDM: Rev:AA



ACAD

PDM: Rev:AA

STATUS: Released

Printed: Oct 28, 2004