

256K nMOS Dynamic RAM (262144×1) 16PIN 6256

型名	社名	温度範囲 (°C)	スイッチング特性								電 源			入力 [*typ]			出力 [*typ]			リフレッシュ Cyc/ms	備 考
			TRAC max (ns)	TRCY min (ns)	TCAD min (ns)	TAH min (ns)	TP min (ns)	TWCY min (ns)	TDDH min (ns)	TRWC min (ns)	VDD or VCC (V)	IDD max (mA)	IDD STANDBY (1 SB/1 SB2) (mA)	VIL max (V)	VIH min (V)	CI max (pF)	VOL / VOL max (V/mA)	VOH / VOH min (V/mA)	Co max (pF)		
MN41256-15	MATSUSHITA	0~70	150	260	25	25	100	260	30	295	4.5~5.5	60	5/-	0.8	2.4	8	0.4/4.2	2.4/5	7	256/4	
MN41256A-10	MATSUSHITA	0~70	100	190	20	100	80	190	20	220	4.5~5.5	70	3/-	0.8	2.4	6	0.4/4.2	2.4/5	5	256/4	
MN41256A-12	MATSUSHITA	0~70	120	220	25	120	90	220	25	255	4.5~5.5	65	3/-	0.8	2.4	6	0.4/4.2	2.4/5	5	256/4	
MN41256A-8	MATSUSHITA	0~70	80	160	20	80	70	160	15	185	4.5~5.5	80	3/-	0.8	2.4	6	0.4/4.2	2.4/5	5	256/4	
MN41256AJ-10	MATSUSHITA	0~70	100	190	20	100	80	190	20	220	4.5~5.5	70	3/-	0.8	2.4	6	0.4/4.2	2.4/5	5	256/4	
MN41256AJ-12	MATSUSHITA	0~70	120	220	25	120	90	220	25	255	4.5~5.5	65	3/-	0.8	2.4	6	0.4/4.2	2.4/5	5	256/4	
MN41256AJ-8	MATSUSHITA	0~70	80	160	20	80	70	160	15	185	4.5~5.5	80	3/-	0.8	2.4	6	0.4/4.2	2.4/5	5	256/4	
MN41256AL-10	MATSUSHITA	0~70	100	190	20	100	80	190	20	220	4.5~5.5	70	3/-	0.8	2.4	6	0.4/4.2	2.4/5	5	256/4	
MN41256AL-12	MATSUSHITA	0~70	120	220	25	120	90	220	25	255	4.5~5.5	65	3/-	0.8	2.4	6	0.4/4.2	2.4/5	5	256/4	
MN41256AL-8	MATSUSHITA	0~70	80	160	20	80	70	160	15	185	4.5~5.5	80	3/-	0.8	2.4	6	0.4/4.2	2.4/5	5	256/4	
MN41257-12	MATSUSHITA	0~70	120	220	25	20	90	220	25	255	4.5~5.5	70	5/-	0.8	2.4	8	0.4/4.2	2.4/5	7	256/4	
MN41257-15	MATSUSHITA	0~70	150	260	25	25	100	260	30	295	4.5~5.5	60	5/-	0.8	2.4	8	0.4/4.2	2.4/5	7	256/4	
MN41257A-10	MATSUSHITA	0~70	100	190	20	100	80	190	20	220	4.5~5.5	70	3/-	0.8	2.4	6	0.4/4.2	2.4/5	5	256/4	
MN41257A-12	MATSUSHITA	0~70	120	220	25	120	90	220	25	255	4.5~5.5	65	3/-	0.8	2.4	6	0.4/4.2	2.4/5	5	256/4	
MN41257A-8	MATSUSHITA	0~70	80	160	20	80	70	160	15	185	4.5~5.5	80	3/-	0.8	2.4	6	0.4/4.2	2.4/5	5	256/4	
MN41257AJ-10	MATSUSHITA	0~70	100	190	20	100	80	190	20	220	4.5~5.5	70	3/-	0.8	2.4	6	0.4/4.2	2.4/5	5	256/4	
MN41257AJ-12	MATSUSHITA	0~70	120	220	25	120	90	220	25	255	4.5~5.5	65	3/-	0.8	2.4	6	0.4/4.2	2.4/5	5	256/4	
MN41257AJ-8	MATSUSHITA	0~70	80	160	20	80	70	160	15	185	4.5~5.5	80	3/-	0.8	2.4	6	0.4/4.2	2.4/5	5	256/4	
MN41257AL-10	MATSUSHITA	0~70	100	190	20	100	80	190	20	220	4.5~5.5	70	3/-	0.8	2.4	6	0.4/4.2	2.4/5	5	256/4	
MN41257AL-12	MATSUSHITA	0~70	120	220	25	120	90	220	25	255	4.5~5.5	65	3/-	0.8	2.4	6	0.4/4.2	2.4/5	5	256/4	
MN41257AL-8	MATSUSHITA	0~70	80	160	20	80	70	160	15	185	4.5~5.5	80	3/-	0.8	2.4	6	0.4/4.2	2.4/5	5	256/4	
M551256-10	MOSEL	0~70	100	100	20	15	85	100	15	200	4.5~5.5	70	4.5/-	0.8	2.4	10	0.4/4.2	2.4/5	7	256/4	
M551256-12	MOSEL	0~70	120	120	22	20	90	120	20	220	4.5~5.5	65	4.5/-	0.8	2.4	10	0.4/4.2	2.4/5	7	256/4	
M551256-15	MOSEL	0~70	150	145	25	25	100	145	25	260	4.5~5.5	57	4.5/-	0.8	2.4	10	0.4/4.2	2.4/5	7	256/4	
MSM37256-15AS	OKI	0~70	150	270	20	45	100	270	45	270	4.5~5.5	75	5/-	0.8	2.4	7	0.4/4.2	2.4/5	7	256/4	
MSM37256-20AS	OKI	0~70	200	330	25	35	120	330	55	330	4.5~5.5	75	5/-	0.8	2.4	7	0.4/4.2	2.4/5	7	256/4	
MSM41256-10ARS/JS	OKI	0~70	100	200	15	20	90	200	20	205											
MSM41256-12ARS/JS	OKI	0~70	120	220	20	20	100	220	20	225	4.5~5.5	65	5/-	0.8	2.4	7	0.4/4.2	2.4/5	7	256/4	
MSM41256-15ARS/JS	OKI	0~70	150	260	25	25	100	260	25	260	4.5~5.5	65	5/-	0.8	2.4	7	0.4/4.2	2.4/5	7	256/4	
MSM41256-20ARS	OKI	0~70	200	330	30	25	120	330	30	330	4.5~5.5	65	5/-	0.8	2.4	7	0.4/4.2	2.4/5	7	256/4	
MSM41257-10ARS/JS	OKI	0~70	100	200	15	20	90	200	20	205											
MSM41257-12ARS/JS	OKI	0~70	120	220	20	20	90	220	20	225											
MSM41257-15ARS/JS	OKI	0~70	150	260	25	25	100	260	25	260											
MT1256-12	MICRON	0~70	120	220	25	20	90	220	40	265	4.5~5.5	75	6/-	0.8	2.4	7	0.4/5	2.4/2	8	256/4	
MT1256-15	MICRON	0~70	150	260	25	25	100	260	45	310	4.5~5.5	75	6/-	0.8	2.4	7	0.4/5	2.4/2	8	256/4	
MT1256-20	MICRON	0~70	200	330	30	30	120	330	55	390	4.5~5.5	75	6/-	0.8	2.4	7	0.4/5	2.4/2	8	256/4	
MT1259-10	MICRON	0~70	90	190	25	100	80	190	35	220	4.5~5.5	55	5/-	0.8	2.4	8	0.4/5	2.4/5	7	256/4	
MT1259-12	MICRON	0~70	100	220	25	120	90	220	40	255	4.5~5.5	55	5/-	0.8	2.4	8	0.4/5	2.4/5	7	256/4	
MT1259-15	MICRON	0~70	120	260	25	150	100	260	45	295	4.5~5.5	45	5/-	0.8	2.4	8	0.4/5	2.4/5	7	256/4	
MT1259-8	MICRON	0~70	75	150	20	80	60	150	15	180	4.5~5.5	65	5/-	0.8	2.4	8	0.4/5	2.4/5	7	256/4	
NMC41257-10	NS	0~70	100	200	20	20	90	200	20	245	4.5~5.5	75	4/-	0.8	2.4	5	0.4/4.2	2.4/5	7	256/4	
NMC41257-12	NS	0~70	120	230	25	30	100	230	25	280	4.5~5.5	75	4/-	0.8	2.4	5	0.4/4.2	2.4/5	7	256/4	