ROPLA 2017.02.20

ALUMINUM ELECTROLYTIC CAPACITORS

APPROVAL NO.


7923


RGB 100 LG 33000 (M)

SERIES	RGB
RATING	100 V 33000 <i>µ</i> F
CASE SIZE	Ø 76.5 × 100 L

A. DIAGRAM OF DIMENSION

[UNIT:mm]





ØD	76.5
L	100
F	31.5

B. MARKING: BLACK SLEEVE & SLIVER INK





RGB 100 V 33000 µF (M) 85 ℃

FRONT VIEW OF CAPACITOR

< SLEEVE or BOTTOM PLATE MARKING >

1 2 3 4

- ① The ending figure of manufactured year in A.D
- ② Manufactured month(1,2,3....9,O,N,D)
- 3 Manufactured day (A,B,C,....Z,a,b,c,d,e)
- SAMYOUNG's symbol NO(1)

C. ELECTRICAL CHARACTERISTICS

A. OPERATING TEMPERATURE RANGE

B. RATED VOLTAGE : $\frac{100 \text{ V}_{DC}}{125 \text{ V}_{DC}}$

D. CAPACITANCE TOLERANCE : ±20% (at 20℃, 120½)

E. LEAKAGE CURRENT : Lower 5000 ∠A , after 5 minutes at 20 ℃

F. DISSIPATION FACTOR (Tan δ) : Lower 0.50 at $20\,^{\circ}$ C, $120\,^{\circ}$ Lz G. RATED RIPPLE CURRENT : 16.1 Arms at $85\,^{\circ}$ C, $120\,^{\circ}$ Lz

H. INSULATION WITHSTANDING VOLTAGE

When a voltage of 2,000V_{AC} is applied for one minute between the terminals shorted each other and the mounting clamp on the insulating sleeve covering the case, there shall not be electrical damage.

I. LOAD LIFE:

The following specifications shall be satisfied when the capacitors are restored to 20 $\,^{\circ}$ C after subjected to DC voltage with the rated ripple current is applied (the peak voltage shall not exceed the rated voltage) 2,000 hours at $85\,^{\circ}$ C.

-40 ~ +85℃

Capacitance change $\leq \pm 20 \%$ of the initial value

Tan δ $\leq \frac{300 \%}{0}$ of the initial specified value

Leakage current ≤ The initial specified value

J. SHELF LIFE:

The following specifications shall be satisfied when the capacitors are restored to 20 $\,^{\circ}$ C after the exposing them at $85\,^{\circ}$ C for 500 hours without voltage applied. The rated voltage shall be applied to the capacitors for a minimum of 30 minutes, at least 24 hours and not more than 48 hours before the measurements.

Capacitance change ≤ ±20 % of the initial value

Tan δ $\leq 300 \%$ of the initial specified value

Leakage current ≤ The initial specified value

K. CLEANING CONDITIONS: Non-solvent proof

L. OTHERS : Satisfied charateristics KS C IEC 60384-4

