**ROPLA** 2019.01.28

# **ALUMINUM ELECTROLYTIC CAPACITORS**

APPROVAL NO.


9687


RGB 200 LG 33000 (M)

SERIES	RGB
RATING	200 V 33000 μF
CASE SIZE	Ø 765 × 170 l

### A. DIAGRAM OF DIMENSION

[UNIT:mm]





## **B. MARKING: BLACK SLEEVE & SLIVER INK**





**RGB** 200 V 33000 μF (M) 85°C

## FRONT VIEW OF CAPACITOR

## < SLEEVE or BOTTOM PLATE MARKING >

1 2 3 4

- 1) The ending figure of manufactured year in A.D.
- 2 Manufactured month(1,2,3....9,O,N,D)
- 3 Manufactured day (A,B,C,...Z,a,b,c,d,e)
- SAMYOUNG's symbol NO(1)

#### C. ELECTRICAL CHARACTERISTICS

A. OPERATING TEMPERATURE RANGE

**B. RATED VOLTAGE** C. SURGE VOLTAGE

D. CAPACITANCE TOLERANCE

**E. LEAKAGE CURRENT** 

F. DISSIPATION FACTOR (Tan δ)

**G. RATED RIPPLE CURRENT** 

<u>- 25</u> ~ <u>+85℃</u>

200 V<sub>DC</sub> 250 V<sub>DC</sub>

±20% (at 20°C, 120Hz)

Lower 5000 µA, after 5 minutes at 20 ℃

Lower <u>0.25</u> at 20℃, 120Hz 18.8 Arms at 85°C, 120Hz

H. INSULATION WITHSTANDING VOLTAGE

When a voltage of 2,000V<sub>AC</sub> is applied for one minute between the terminals shorted each other and the mounting clamp on the insulating sleeve covering the case, there shall not be electrical damage.

I. LOAD LIFE: The following specifications shall be satisfied when the capacitors are restored to 20°C after subjected to DC voltage with the rated ripple current is applied (the peak voltage shall not

# Capacitance change  $\leq \pm 20 \%$  of the initial value

# Tanδ ≤ 300 % of the initial specified value

exceed the rated voltage) for 2,000 hours at 85℃.

# Leakage current ≤ The initial specified value

J. SHELF LIFE  $\,:$  The following specifications shall be satisfied when the capacitors are restored to 20  $^\circ$ C after the exposing them at 85°C for 500 hours without voltage applied.

The rated voltage shall be applied to the capacitors for a minimum of 30 minutes,

at least 24 hours and not more than 48 hours before measurements.

# Capacitance change  $\leq \pm 20 \%$  of the initial value

≤ 300 % of the initial specified value

# Leakage current ≤ The initial specified value

K. CLEANING CONDITIONS: Non-solvent proof

L. OTHERS : Satisfied charateristics KS C IEC 60384-4

