ROPLA 2020.12.17

ALUMINUM ELECTROLYTIC CAPACITORS

APPROVAL NO.


11602


RGB 400 LG 4700 (V)

SERIES	RGB
RATING	400 V 4700 μF
CASE SIZE	Ø 76.5 × 105 L

A. DIAGRAM OF DIMENSION

[UNIT:mm]





B. MARKING: <u>BLACK</u> SLEEVE & <u>SLIVER</u> INK





400 V 4700 μF (V) 85 ℃

FRONT VIEW OF CAPACITOR

< SLEEVE or BOTTOM PLATE MARKING >

(1) (2) (3) (4)

- ① The ending figure of manufactured year in A.D
- ② Manufactured month(1,2,3....9,O,N,D)
- 3 Manufactured day (A,B,C,....Z,a,b,c,d,e)
- **4** SAMYOUNG's symbol NO(1)

C. ELECTRICAL CHARACTERISTICS

A. OPERATING TEMPERATURE RANGE

B. RATED VOLTAGE C. SURGE VOLTAGE

D. CAPACITANCE TOLERANCE

E LEAKAGE OURDENT

E. LEAKAGE CURRENT

F. DISSIPATION FACTOR (Tan δ) G. RATED RIPPLE CURRENT

G. RATED RIPPLE CURRENT

H. INSULATION WITHSTANDING VOLTAGE

: <u>- 25</u> ~ <u>+85℃</u>

400 V_{DC}

450 V_{DC}

-10% ~ +20% (at 20℃, 120Hz)

Lower 5000 μ A, after 5 minutes at 20 $^{\circ}$ C

Lower <u>0.25</u> at 20℃, 120Hz

11.7 Arms at 85°C, 120Hz

When a voltage of 2,000V_{AC} is applied for one minute between the terminals shorted each other and the mounting clamp on the insulating sleeve covering the case, there shall not be electrical damage.

I. LOAD LIFE : The following specifications shall be satisfied when the capacitors are restored to 20 ℃ after subjected to DC voltage with the rated ripple current is applied (the peak voltage shall not exceed the rated voltage) for 2,000 hours at 85 ℃.

Capacitance change $\leq \pm 20 \%$ of the initial value

Tan δ \leq 300 % of the initial specified value

Leakage current ≤ The initial specified value

J. SHELF LIFE: The following specifications shall be satisfied when the capacitors are restored to 20°C after the exposing them at 85°C for 500 hours without voltage applied.

The rated voltage shall be applied to the capacitors for a minimum of 30 minutes, at least 24 hours and not more than 48 hours before measurements.

Capacitance change $\leq \pm 20 \%$ of the initial value

Tan δ $\leq 300 \%$ of the initial specified value

Leakage current ≤ The initial specified value

K. CLEANING CONDITIONS: Non-solvent proof

L. OTHERS : Satisfied charateristics KS C IEC 60384-4

